



P/N LEGEND

A1252	WR	-XP	N	0	B	T1	N	00	B
①	②	③	④	⑤	⑥	⑦	⑧	⑨	⑩

① Series No.
 ② Connector type: WR=Right angle
 ③ No. of circuits
 ④ N=Halogen Free
 ⑤ Material: 0=Nylon66 94-V0+GF15%
 ⑥ Color: B=Black
 ⑦ Plating code for contacts: T1=Tin-plated
 ⑧ Plating code: N=Non-plating
 ⑨ Option code: 00=Standard
 ⑩ Packing code: B=Tray

SPECIFICATIONS

Current Rating: 1A AC,DC
 Voltage Rating: 150V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 30mΩ Max.
 Insulation Resistance: 500MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Pin Material: Brass

Circuit No.	Dimensions		
	A	B	C
02P	1.25	3.75	3.15
03P	2.50	5.00	4.40
04P	3.75	6.25	5.65
05P	5.00	7.50	6.90
06P	6.25	8.75	8.15
07P	7.50	10.00	9.40
08P	8.75	11.25	10.65
09P	10.00	12.50	11.90
10P	11.25	13.75	13.15
11P	12.50	15.00	14.40
12P	13.75	16.25	15.65
13P	15.00	17.50	16.90
14P	16.25	18.75	18.15
15P	17.50	20.00	19.40

				UNIT	SCALE	SHEET	TITLE:
				mm	1 : 1	1 of 1	
DRAWN BY		APPROVED BY		<p style="text-align: center;">1.25mm PITCH 90° SINGLE ROW WAFER</p>			
劉建芳		謝瑞清					
2016.06.06		2016.06.06					
GENERAL TOLERANCE				DRAW NO. :			
A1	ECN1607210001	2016.07.21	Emily	X. X±0.25	ANGLE±		A1252WR-XPXXXXXXXXXX
A0	NEW RELEASE	2016.06.06	劉建芳	X. XX±0.15			
REV.	DESCRIPTION	DATE	NAME	X. XXX±0.05			

A
B
C
D

A
B
C
D

1 | 2 | 3 | 4 |

1 | 2 | 3 | 4 |