



P/N LEGEND

A2016	HR-2XNP	R	6	B	G1	N	D0	B	
①	②	③	④	⑤	⑥	⑦	⑧	⑨	⑩

① Series No.
 ② Connector type: HR=Right Angle
 ③ No. of circuits
 ④ R=RoHS
 ⑤ Material: 6=Nylon 6T, UL94V-0
 ⑥ Color: B=Black
 ⑦ Plating code for contacts: G1=Gold-Flash
 ⑧ Plating code: N=Non-plating
 ⑨ Option code: D0=D0 Type
 ⑩ Packing code: B=Tray

SPECIFICATIONS

Current Rating: 3A AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage: 1000V AC/minute
 Pin Material: Brass

				 燦達電子工業股份有限公司 JOINT TECH ELECTRONIC IND. CO., LTD.	
UNIT	SCALE	SHEET	TITLE:		
mm	1 : 1	1 of 1	2.00mm PITCH 90° WAFER		
DRAWN BY		APPROVED BY			
周傑亮		陳彥兆			
2015.01.09		2015.01.09	DRAW NO. : A2016HR-2XNPR6BG1ND0B		
GENERAL TOLERANCE					
X. X±0.30		ANGLE±			
X. XX±0.20				REV. A0	
X. XXX±0.10				REV. A0	
A0	NEW RELEASE	2015.01.09	周傑亮		
REV.	DESCRIPTION	DATE	NAME		