



P/N LEGEND

<u>A2540</u>	<u>H</u> - <u>XP</u>	<u>N</u>	<u>0</u>	<u>W</u>	<u>NP</u>	<u>N</u>	<u>00</u>	<u>G</u>	
①	②	③	④	⑤	⑥	⑦	⑧	⑨	⑩

① Series No.  
 ② Connector type: H=Housing  
 ③ No. of circuits  
 ④ N=Halogen Free  
 ⑤ Material: 0=Nylon 66-V0  
 ⑥ Color: W=White  
 ⑦ Plating code: NP=Non-plating  
 ⑧ Plating code: N=Non-plating  
 ⑨ Option code: 00=Standard  
 ⑩ Packing code: G=Bag

SPECIFICATIONS

Current Rating: 3A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 10mΩ Max  
 Insulation Resistance: 500MΩ Min  
 Withstanding Voltage: 800V AC/minute  
 Material: Nylon 66,UL94V-0  
 Color: White

Circuit No.	Dimensions		
	A	B	C
02P	2.50	7.25	5.90
03P	5.00	9.75	8.40
04P	7.50	12.25	10.90
05P	10.00	14.75	13.40
06P	12.50	17.25	15.90
07P	15.00	19.75	18.40
08P	17.50	22.25	20.90
09P	20.00	24.75	23.40
10P	22.50	27.25	25.90
11P	25.00	29.75	28.40
12P	27.50	32.25	30.90
13P	30.00	34.75	33.40
14P	32.50	37.25	35.90
15P	35.00	39.75	38.40

燦達電子工業股份有限公司 JOINT TECH ELECTRONIC IND. CO., LTD.				UNIT	SCALE	SHEET	TITLE:
				mm	1 : 1	1 of 1	
DRAWN BY		APPROVED BY		GENERAL TOLERANCE		2.50mm PITCH HOUSING	
陳敏		董正一					
2011.08.08		2011.08.08					
X. X±0.25		ANGLE±					
X. XX±0.15				DRAW NO. :		REV. AO	
X. XXX±0.05				A2540H-XPNXXXXXXXXX			
AO	NEW RELEASE	2011.08.08	陳敏				
REV.	DESCRIPTION	DATE	NAME				