


TYPE 2



SPECIFICATIONS

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 500MΩ Min
 Withstanding Voltage: 800V AC/minute
 Pin Material: Brass/Tin-plated
 Material: Nylon 66,UL94V-0
 Color: White

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
A2540WR-02PN2	2.50	5.00
A2540WR-03PN2	5.00	7.50
A2540WR-04PN2	7.50	10.00
A2540WR-05PN2	10.00	12.50
A2540WR-06PN2	12.50	15.00
A2540WR-07PN2	15.00	17.50
A2540WR-08PN2	17.50	20.00
A2540WR-09PN2	20.00	22.50
A2540WR-10PN2	22.50	25.00
A2540WR-11PN2	25.00	27.50
A2540WR-12PN2	27.50	30.00
A2540WR-13PN2	30.00	32.50
A2540WR-14PN2	32.50	35.00
A2540WR-15PN2	35.00	37.50

UNIT	SCALE	SHEET	TITLE:	
mm		1 of 1	2.50mm PITCH 90° WAFER	
DRAWN BY		APPROVED BY		
歐陽小強 2008.09.16		謝瑞清 2008.09.16		
GENERAL TOLERANCE				
X. X±0.25		ANGLE±		
X. XX±0.15				
X. XXX±0.05				
A0	NEW RELEASE	2008.09.16	DRAW NO. : A2540WR-XPN2	
REV.	DESCRIPTION	DATE	REV. A0	